

STROBE SMALL BEACON

	PART.NO.	FLASH PATTERN	COLOUR	CURRENT DRAW @ 12V	OPERATING VOLTAGE	JOULES	FLASHTUBE	DIMENSIONS
	S1211AB	Single	Amber	0.25 Amps	12-80 VDC	1.5 J/s (1.9 W/s)	L4613D	95mm (H)
	S1221AB	Double		0.5 Amps	12-80 VDC	1.4 J/s (1.7 W/s)	L4614B	129mm (D)
	S1231AB	Triple		0.5 Amps	12-80 VDC	1.5 J/s (1.9 W/s)	L4614B	
	S1211BB	Single	Blue	0.25 Amps	12-80 VDC	1.5 J/s (1.9 W/s)	L4613D	95mm (H)
	S1221BB	Double		0.5 Amps	12-80 VDC	1.4 J/s (1.7 W/s)	L4614B	129mm (D)
	S1231BB	Triple		0.5 Amps	12-80 VDC	1.5 J/s (1.9 W/s)	L4614B	
	S1211CB	Single	Clear	0.25 Amps	12-80 VDC	1.5 J/s (1.9 W/s)	L4613D	95mm (H)
	S1221CB	Double		0.5 Amps	12-80 VDC	1.4 J/s (1.7 W/s)	L4614B	129mm (D)
	S1231CB	Triple		0.5 Amps	12-80 VDC	1.5 J/s (1.9 W/s)	L4614B	
	S1211GB	Single	Green	0.25 Amps	12-80 VDC	1.5 J/s (1.9 W/s)	L4613D	95mm (H)
	S1221GB	Double		0.5 Amps	12-80 VDC	1.4 J/s (1.7 W/s)	L4614B	129mm (D)
	S1231GB	Triple		0.5 Amps	12-80 VDC	1.5 J/s (1.9 W/s)	L4614B	
	S1211RB	Single	Red	0.25 Amps	12-80 VDC	1.5 J/s (1.9 W/s)	L4613D	95mm (H)
	S1221RB	Double		0.5 Amps	12-80 VDC	1.4 J/s (1.7 W/s)	L4614B	129mm (D)
	S1231RB	Triple		0.5 Amps	12-80 VDC	1.5 J/s (1.9 W/s)	L4614B	

- PC Board is epoxy potted to extend the lifespan of the beacon.
- Also available as a magnetic beacon.
- To ensure that moisture does not affect the operation of the beacon, always check that the O-ring is in the correct position.

1000 SERIES REPLACEMENT PARTS

							
BRANCH GUARD	MAGNETIC KIT	POLE MOUNT	AMBER LENS	BLUE LENS	CLEAR LENS	GREEN LENS	RED LENS
1200BG	1200M-KIT	1200PM	1200AL	1200BL	1200CL	1200GL	1200RL

TECHNICAL DRAWING

