

## STROBE TALL BEACON

	PART.NO.	FLASH PATTERN	COLOUR	CURRENT DRAW @ 12V	OPERATING VOLTAGE	JOULES	FLASHTUBE	DIMENSIONS
	S2211AB	Single	Amber	0.5 Amps	12-80 VDC	1.9 J/s (2.4 W/s)	2010FT	130mm (H) 74mm (D)
	S2211BB	Single	Blue	0.5 Amps	12-80 VDC	1.9 J/s (2.4 W/s)	2010FT	130mm (H) 74mm (D)
	S2211CB	Single	Clear	0.5 Amps	12-80 VDC	1.9 J/s (2.4 W/s)	2010FT	130mm (H) 74mm (D)
	S2211GB	Single	Green	0.5 Amps	12-80 VDC	1.9 J/s (2.4 W/s)	2010FT	130mm (H) 74mm (D)
	S2211RB	Single	Red	0.5 Amps	12-80 VDC	1.9 J/s (2.4 W/s)	2010FT	130mm (H) 74mm (D)

- PC Board is epoxy potted to extend the lifespan of the beacon.
- To ensure that moisture does not affect the operation of the beacon, always check that the O-ring is in the correct position.

## 2000 SERIES REPLACEMENT PARTS

				
<b>AMBER LENS</b>	<b>BLUE LENS</b>	<b>CLEAR LENS</b>	<b>GREEN LENS</b>	<b>RED LENS</b>
2200AL	2200BL	2200CL	2200GL	2200RL

## TECHNICAL DRAWING

